

Akustiq Click 1220x180x5/0.5



Specification	QC Standard	Method
Heterogene PVC	virgin PVC	EN 649
Click	Unilin	
UV Coating	yes	
ISO 9001	yes	
Demension	1220mm x 180mm	EN 427
Length Deviation	±0.5mm	EN 427
Width Deviation	±0.15mm	EN 427
Total thickness	5mm	EN 427
Total thickness Deviation	±0.15mm	EN 427
Weight	ca. 9.81 Kg /m ²	EN 430
Wear layer thickness	0.5mm	EN 429
Wear layer thickness deviation	±0.02mm	EN 429
Squareness and Straightness for side length	≤400mm, ≤0.25mm; >400mm, ≤0.35mm	EN 427
Height Difference	ha≤0.1mm, hmax≤0.15mm	
Initial curling	-1.0≤n≤0.5mm	EN 434
Curling after exposure to heat	M type:≤2.0mm; W type:≤8.0mm	EN 434
Dimensional stability	M type:≤0.25%; W type:≤0.40%	EN 434
Peeling Strength	≥1.5kgf/cm	EN 431
Use Classification	23/33	EN 685
Residual Indentation	≤0.10mm	EN 433
Fire Resistance	Bfl-s1	EN 13501-1
Static electrical charge	<2KV	EN 1815
Roll chair resistance	Suitable	EN 425
Slip resistance	R9	ADA
Flooring Heating	Max.27° Celsius	
Gloss Level	6 to 8 depending on decor	ISO 105/B02
Toxic Element Limit	not toxic, class 0	EN 71
Damage, Chipping, Wrinkle, Pin hole	Not allowed	GB/T 4085& EN649:1997
Delamination, Peeling	Not allowed	
Impurity,Bubble,Scratch, Discolor,Dent,Stain,etc,	Not Visually Apparent(View from 70cm,not more than 1	
Off-register	≤1mm	
White Edge on Surface	Not allowed	