



**4121 - 4124**

**Plank with integrated underlay**

**Product information**

Clicksystem	Loc-Click
Chamfer	bevelled
Sealing	UV varnish
Wear layer	0.5 mm
Utilisation class	41

**Technical data**

Dimension		1220 x 226 x 5 mm
Packing unit (PU)	Wide Plank	8 Planks = 2.206 sqm
Pallet size		48 PU = 105.88 sqm

**Test results**

Lightfast	ISO 105-B02	≥ 8
Dimensional stability	ISO 23999	✓
Fire behavior	EN 13501-1	Bfl, s1
Straightness and squareness	ISO 24337	≤ 0.25 mm
Residual indentation	ISO 24342	0.18 mm
Slip resistance	EN 14041	DS
Thermal Conductivity	EN 12667	0.085 W/(m·K)
Underfloor heating	EN 12667	Suitable for hot water, max 27 degrees
Formaldehyde class	EN 717-1	E1 < 0.05 ppm
Chair caster suitability	EN 425	no damage

All specified values are standard values.  
Production-related fluctuations can not be ruled out.



Scheuten-Solar-Str. 2 • 45881 Gelsenkirchen • Tel.: +49 209 / 59034-0 • Fax: +49 209 / 59034-29

E-Mail: [info@koczwara-vertrieb.de](mailto:info@koczwara-vertrieb.de) • Web: [www.koczwara-vertrieb.de](http://www.koczwara-vertrieb.de)